

Grooveline BPIR Declaration

Version: v1

Designated building product: Class 1

Declaration

SKAPE LIMITED has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

| Name | Grooveline |
|------------|------------|
| Line | |
| Identifier | GROOVELINE |

Description

Experience the timeless appeal of tongue and groove panelling with Grooveline, designed for quick and cost-effective installation.

With V-grooves at 100mm intervals, these versatile panels can be installed vertically or horizontally to achieve various design effects. They are suitable for painting or can be left natural with a polyurethane or oiled finish.

Available untreated or treated for both indoor and outdoor use.

FEATURES

- V-Grooves 3-5mm at 100mm centres
- Non-structural plywood
- Warm golden brown appearance
- Available untreated and treated H3.1 LOSP

BENEFITS

- B/D Paint Grade Finish takes stains, paint, oils and polyurethanes well
- Easy installation using tongue & groove



DIMENSIONS

Sheet Size Thickness 2400 x 1200 mm 9, 12 mm

All panel sizes are available untreated or treated H3.1 LOSP.

Scope of use

- · Wall and ceiling lining
- Soffitlining

Conditions of use

- Untreated Grooveline should not be used where it will be subject to wetting, dampness or condensation.
- In areas where Grooveline may be subject to wetting, dampness or condensation Grooveline must be preservative treated to at least H3.2 hazard rating and fixed with non-corrosive fasteners.

Relevant building code clauses

B1 Structure – B1.3.1, B1.3.2, B1.3.3 (j), B1.3.4

F2 Hazardous building materials - F2.3.1

Contributions to compliance

- B2 Durability B2.3.1 (c)
- F2 Hazardous Building Materials F2.3.1
- B2/AS1 Table 1.
- F2 AS/NZ 2269



Supporting documentation

The following additional documentation supports the above statements:

For further information supporting Grooveline claims refer to our website.

Contact details

| Manufacture location | Overseas |
|--|--------------------------------|
| Legal and trading name of manufacturer | ARAUCO |
| Legal and trading name of importer | SKAPE LIMITED |
| Importer address for service | 27 Poporo Way Hastings 4175 |
| Importer website | www.skape.co.nz |
| Importer NZBN | 9429052619854 |
| Importer email | sales@skape.co.nz |
| Importer phone number | |

Building code performance clauses

B1 Structure

B1.3.1

Buildings, *building elements* and *sitework* shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction* or *alteration* and throughout their lives.



B1.3.2

Buildings, *building elements* and *sitework* shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings*, *building elements* and *sitework*, including:

• (j) impact

B1.3.4

Due allowances shall be made for:

- a. the consequences of failure,
- b. the intended use of the building,
- c. effects of uncertainties resulting from *construction* activities, or the sequence in which *construction* activities occur,
- d. variation in the properties of materials and the characteristics of the site, and
- e. accuracy limitations inherent in the methods used to predict the stability of buildings

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.