

DECLARATION OF PERFORMANCE

in accordance with Annex III - COMMISSION DELEGATED REGULATION (EU) No 574/2014

DOP No.: **DOP-TK-HEX1-250604**

1. Unique identification code of the product-type: TEKCOM TEKCOM HEXA PLY ADVANCED
2. Intended use/es: Plywood for external use as structural components
3. Material(s): 100% rubberwood veneer
4. Manufacturer details - Name: TEKCOM CORPORATION
5. Contact address: Lot A1-A2-A3-A4-A5, N5 Street, Nam Tan Uyen Expansion Industrial Park, Hoi Nghia Hamlet, Tan Uyen City, Binh Duong Province, Vietnam
6. Authorised representative: Not Relevant
7. System/s of AVCP: System 2+
8. Harmonised standard: EN 13986:2014 + A1:2015
9. Notified body/ies: NB 0407 - STITUTO GIORDANO S.p.A.
10. European Assessment Document: Not Relevant
11. Declared performance/s: based on EN 13986:2004 + A1:2015 harmonised technical specification for AVCP system 2+

No.	Essential characteristics	Performance	Harmonised technical specification
1	Bending strength - Lengthwise - Widthwise	≥ 40 N/mm ² ≥ 50 N/mm ²	EN 13986:2014 + A1:2015
2	Bending stiffness (Modulus of elasticity) - Lengthwise - Widthwise	$\geq 4,000$ N/mm ² $\geq 5,000$ N/mm ²	
3	Bonding quality	Class 3	
4	Internal bond (Tensile strength)	NPD	
5	Durability (Swelling in thickness)	NPD	
6	Durability (Moisture resistance)	NPD	
7	Release of formaldehyde	E1	
8	Reaction to fire	D-s2, d0	
9	Water vapour permeability	NPD	
10	Airborne sound insulation	NPD	
11	Sound absorption	NPD	
12	Thermal conductivity	NPD	
13	Strength and stiffness to structural use	NPD	
14	Mechanical durability	NPD	
15	Biological durability	NPD	
16	Content of pentachlorophenol	PCP \leq 5ppm	

TEKCOM Corporation

TEKCOM BD1: Lot M1-M2-M7-M8, N2-N3 Street,
 TEKCOM BD2: Lot A1-A2-A3-A4-A5, N5 Street,
 Nam Tan Uyen Expansion IP, Hoi Nghia Hamlet, Tan Uyen Town, Binh Duong Province, Vietnam.
 www.tekcom.vn | info@tekcom.vn | (+84) 977 668 000



17	Racking resistance	NPD	
18	Embedment strength	NPD	

Information according to Article 31 and Article 33 of Regulation (EC) No. 1907/2006 (REACH)

The products referred to by this DoP can be classified as "articles" according to Reach and, therefore, Article 31 of Reach does not apply (e.g.: no SDS has to be provided). In addition, the above-mentioned products do not intentionally release any substances during normal use and do not contain:

- SVHCs;
- substances listed in Annex XIV of Reach;
- substances listed in Annex XVII of Reach;

therefore, no specific information nor warning has to accompany the products.

Note: point 6b and 8 of Annex III - COMMISSION DELEGATED REGULATION (EU) No 574/2014 are not applicable.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At TEKCOM CORPORATION on June, 4th, 2025




Nguyễn Hữu Linh

TEKCOM Corporation

TEKCOM BD1: Lot M1-M2-M7-M8, N2-N3 Street,
 TEKCOM BD2: Lot A1-A2-A3-A4-A5, NS Street,
 Nam Tan Uyen Expansion IP, Hoi Nghia Hamlet, Tan Uyen Town, Binh Duong Province, Vietnam.
 www.tekcom.vn | info@tekcom.vn | (+84) 977 668 000

CE MARKING

 NB: 0407	
25	
TEKCOM CORPORATION Lot A1-A2-A3-A4-A5, N5 Street, Nam Tan Uyen Expansion Industrial Park, Hoi Nghia Hamlet, Tan Uyen City, Binh Duong Province, Vietnam	
DOP No.: DOP-TK-HEX1-250604 EN 13986:2014 + A1:2015 Intended use: Plywood for external use as structural components System 2+	
TEKCOM HEXA PLY ADVANCED	
Bending strength	
- Lengthwise	$\geq 40 \text{ N/mm}^2$
- Widthwise	$\geq 50 \text{ N/mm}^2$
Bending stiffness (Modulus of elasticity)	
- Lengthwise	$\geq 4,000 \text{ N/mm}^2$
- Widthwise	$\geq 5,000 \text{ N/mm}^2$
Bonding quality	Class 3
Internal bond (Tensile strength)	NPD
Durability (Swelling in thickness)	NPD
Durability (Moisture resistance)	NPD
Release of formaldehyde	E1
Reaction to fire	D-s2, d0
Water vapour permeability	NPD
Airborne sound insulation	NPD
Sound absorption	NPD
Thermal conductivity	NPD
Strength and stiffness to structural use	NPD
Mechanical durability	NPD



TEKCOM Corporation

TEKCOM BD1: Lot M1-M2-M7-M8, N2-N3 Street,
 TEKCOM BD2: Lot A1-A2-A3-A4-A5, N5 Street,
 Nam Tan Uyen Expansion IP, Hoi Nghia Hamlet, Tan Uyen Town, Binh Duong Province, Vietnam.
 www.tekcom.vn | info@tekcom.vn | (+84) 977 668 000

Biological durability	NPD
Content of pentachlorophenol	PCP \leq 5ppm
Racking resistance	NPD
Embedment strength	NPD

TEKCOM Corporation

TEKCOM BD1: Lot M1-M2-M7-M8, N2-N3 Street,
 TEKCOM BD2: Lot A1-A2-A3-A4-A5, NS Street,
 Nam Tan Uyen Expansion IP, Hoi Nghia Hamlet, Tan Uyen Town, Binh Duong Province, Vietnam.
www.tekcom.vn | info@tekcom.vn | (+84) 977 668 000