

# EzyForm

Film faced plywood is a building material that is widely used in concrete construction for concreting vertical, horizontal and inclined formwork structures: foundations, walls and floors. Thanks to the film-face, the plywood has increased moisture resistance and wear resistance properties and improves strength characteristics.

EzyForm is a versatile choice for various construction projects. Its durable black film face enhances the smoothness of concrete finishes, providing a neat and clean look. This offers added protection against moisture and wear, and with proper maintenance, it can be used multiple times, making it a cost-effective option for budget-conscious builders.



# EzyForm

## PROPERTIES

Dimensions	2440 x 1220 x 18mm, 11 plies
Structural Rating	Non structural
Wood Materials	Legally sourced plantation wood, FSC
Film Color	Dark Brown, Black and Brown

## FILM DENSITY: (BLACK ON 2 FACES) 40/135GSM

Density	559kg/m <sup>3</sup>
Formaldehyde Emission Class	E1
Glue	Exterior, WBP, MUF (Melamine Urea Formaldehyde)
Edge Treatment	Waterproof Paint
Moisture Content	< 12%
Core Veneer	Acacia or Eucalyptus
Number of Cycles	> 12 (if applied, handled and maintained correctly)
Hardness	5900-6800 MPA

## HANDLING AND STORAGE

Boards can be cleaned with warm water after use to remove any remaining material adhered to the surface. They must be stored on a hard, flat surface, avoiding direct contact with the ground and in a dry environment protected from water. Sudden changes in these conditions can affect the properties of the board. Separate the boxes from each other with clean, dry and resistant spacers of uniform thickness, suitable for loading/unloading with forklift.

**Skape.**  
PANELS

Postal address: Skape Panels Limited, 34  
Leonard Road, Mt Wellington, Auckland 1060.

[www.skape.co.nz](http://www.skape.co.nz) | [sales@skape.co.nz](mailto:sales@skape.co.nz)

